STAINLESS RESTORATION LTD

STAINLESS STEEL CLEANER - EXTRA


enerjex 410

PRODUCT:
ENERJEX 410

APPLICATION:
200, 300, 400 SERIES STAINLESS STEELS
DUPLEX STAINLESS STEELS
NICKEL ALLOYS
ALUMINIUM ALLOYS

FOR SUITABILITY ON OTHER METALS PLEASE CONSULT OUR SALES DESK

GENERAL:



ENERJEX 410 is a more aggressive cleaner than its close relative, ENERJEX 425. Ideal for removing surface contaminates such as:

Light oil
Anti-spatter residue
Grease
Residue from dye penetrant system testing
Lay-out ink
Marker pen
Dirt, hand & foot prints
Free “iron” (light tooling marks, iron scratches, “Tea” staining etc)

Dirt or other contaminates left on the surface will inhibit the pickling or passivation and may result in an uneven etch. SRL regard this product as a” SEMI - PICKLE” system since its has a mild, but positive, etching effect.
Can be used as a stand alone cleaner/passivator for any of the alloys listed above. A distinct change in the surface “lustre”will be evident after application. A much more powerful cleaner than most cleaners.

CHEMICAL PROPERTIES:

Composition:	Phosphoric Acid based blend. Wetting agent
Form:	Liquid
Density:	1.1 kg/l
pH:	1
Flash point:	-




STAINLESS RESTORATION LTD


STAINLESS STEEL CLEANER - EXTRA

enerjex 410


HOW TO USE:




Apply with brush, spray or dipping.
Warning: The entire surface must be covered to ensure an even shade. Streaks and omitted areas will look different.



The recommended working minimum contact time is 10 - 15 minutes.
longer times can be used. care must be taken not to allow to dry on the surface.



Rinse thoroughly with plenty of water.



The waste water should have a pH value between 6 and 10 before disharge.
Use ENERJEX 520 for neutralization of acid waste.
Always consult your local water authority for correct disharge values.

PACKAGING:

ENERJEX 410 is supplied in 25lt, 200lt and 1000lt containers
All containers are UN certified and carry correct labelling.

STORAGE:

ENERJEX 410 should be stored indoors at room temperature. Containers must be kept in an upright position with the caps properly sealed and away from unauthorised persons.

SAFETY FIRST:

As always when using chemicals proper protective clothing must be worn. See Safety Data (SDS) sheets. Only trained persons should use this product.

ENVIRONMENT:

The waste produced after cleaning needs to be collected and neutralised before entering the public sewage system. Stainless Restoration Ltd offer neutralizing products to assist in this cause. Stainless Restoration Ltd will give advice FREE of charge concerning the disposal issue.
See Safety Data (SDS) sheets.

Information given in this leaflet may be subject to alteration without notice
care has been taken to ensure that the contents of this publication are accurate but Stainless Restoration Ltd do not accept responsibility for error or for information which is found to be misleading. Suggestions for or descriptions of the end use or application of products or methods of working are for information only and the company accept no liability in respect therof. Before using products supplied or manufactured by the company the customer should satisfy himself of their suitability. If further assistance is required, the company which has access to extensive research facilities, will often be willing to help.

Stainless Restoration Ltd
Unit M1 Adamson Industrial Estate, Croft Street, Hyde, Cheshire SK14 1EE
Tel: 0161 368 6191 Fax: 0161 366 9790 www.stainrest.com